

IN THE CLAIMS

Please amend the claims to read as indicated below.

1. (previously presented) A method for correcting a measured signal transmitted through a system, said method comprising:

sampling said measured signal to yield a sampled signal sequence;
reproducing said sampled signal sequence to yield a plurality of copies of said sampled signal sequence;
appending said plurality of copies to one another to yield a signal series;
windowing said signal series with a window function to yield a windowed signal series; and
recalculating a corrected measured signal from said windowed signal series using information about a frequency-dependency of said system.

2. (previously presented) The method of claim 1, wherein said recalculating a corrected measured signal from said windowed signal further comprises:

transforming said windowed signal series from a time domain into a frequency domain to yield a transformed signal series;
modifying said transformed signal series with a transfer function as a function of frequency of said system to yield a modified transformed signal series;
re-transforming said modified transformed signal series back from said frequency domain into said time domain to yield a re-transformed signal series; and
receiving said corrected measured signal from said re-transformed signal series.

3. (previously presented) The method of claim 1, wherein said recalculating a corrected measured signal from said windowed signal further comprises modifying said corrected measured signal with a function inverse to said window function.

4. (previously presented) The method of claim 2, wherein said receiving said corrected measured signal from said re-transformed signal series further comprises selecting a corrected signal sequence from said re-transformed signal series substantially corresponding to said sampled signal sequence.

5. (previously presented) The method of claim 4, wherein said selected corrected signal sequence is selected substantially from a middle range of said re-transformed signal series.

6. (previously presented) The method according to claim 1, wherein said sampling said measured signal is executed by a measuring device at a highest accuracy provided by said measuring device.

7. (previously presented) A method for correcting a measured signal transmitted through a system having a transfer function as a function of frequency, said method comprising:

sampling said measured signal to yield a sampled signal sequence;
reproducing said sampled signal sequence to yield a plurality of copies of said sampled signal sequence;
appending said plurality of copies to one another to yield a signal series;
windowing said signal series with a window function to yield a windowed signal series;
transforming said windowed signal series from a time domain into a frequency domain to yield a transformed signal series;
modifying said transformed signal series with said transfer function of said system to yield a modified transformed signal series;
re-transforming said modified transformed signal series back from said frequency domain into said time domain to yield a re-transformed signal series; and
receiving a corrected measured signal from said re-transformed signal series.

8. (previously presented) A method for providing a measured signal for further processing, said method comprising:

sampling said measured signal to yield a sampled signal sequence;
reproducing said sampled signal sequence to yield a plurality of copies of said sampled signal sequence;
appending said plurality of copies to one another to yield a signal series; and
processing said signal series to determine a characteristic of said measured signal.

9. (currently amended) ~~A software program storable on a data carrier, for executing a method when operated in a computer system, said method comprising~~ A data carrier, comprising:
a program that controls a processor to execute a method that includes:

~~sampling said a measured signal that is transmitted through a system,~~ to yield a sampled signal sequence;
reproducing said sampled signal sequence to yield a plurality of copies of said sampled signal sequence;

appending said plurality of copies to one another to yield a signal series;
windowing said signal series with a window function to yield a windowed signal series; and
recalculating a corrected measured signal from said windowed signal series using information about a frequency-dependency of said system.

10. (previously presented) An apparatus for executing a method for correcting a measured signal, said apparatus comprising:

a sampling device for sampling said measured signal to yield a sampled signal sequence;
a signal multiplication unit for reproducing said sampled signal sequence to yield a plurality of copies of said sampled signal sequence, and appending said plurality of copies to one another to yield a signal series;
a device for performing windowing functions for windowing the signal series with a window function to yield a windowed signal series; and
a recalculation unit for recalculating a corrected measured signal from said windowed signal series using information about a frequency-dependency of said system.

11. (previously presented) An apparatus for correcting a measured signal transmitted through a system comprising:

means for sampling said measured signal to yield a sampled signal sequence;
means for reproducing said sampled signal sequence to yield a plurality of copies of said sampled signal sequence;
means for appending said plurality of copies to one another to yield a signal series;
means for windowing said signal series with a window function to yield a windowed signal series; and
means for recalculating a corrected measured signal from said windowed signal series using information about a frequency-dependency of said system.

12. (previously presented) The method of claim 1, wherein said measured signal is a high speed digital pulse.

13. (previously presented) The method of claim 7, wherein said measured signal is a high speed digital pulse.

14. (previously presented) The method of claim 8, wherein said measured signal is a high speed digital pulse.

15. (previously presented) The apparatus of claim 11, wherein said measured signal is a high speed digital pulse.